# SAFETY DATA SHEET

#### Issuing Date 15-Dec-2014 Revision Date 6-Jan-2016 **Revision Number** 1 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING **GHS Product Identifier** Product Name: **Ready To Use Asphalt Sealer** Other Means of Identification Product Code(s): T5 Synonyms None Recommended Use of the Chemical and Restrictions on Use Recommended Use: No Information Available **Uses Advised Against:** No information Available Supplier's Details Supplier Address Team Laboratory Chemical Corporation 28650 State Highway 34 Detroit Lakes, MN 56501 1-800-522-8326 **Emergency Telephone Number** Infotrac: 1-800-535-5053 2. **HAZARDS IDENTIFICATION**

#### **Classification**

This product is not considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

		Emergency Overview	
Signal Word	Warning		
•Ma Appearance: Black	rmful if swallowed ay cause skin irritation	Physical State: Liquid	Odor: Aspha
Precautionary Statement Prevention	s Inhalation: Eye Contact: Skin Contact: Ingestion:	May cause irritation of respiratory tract. Contact with eyes may cause irritation. May cause irritation. Ingestion may cause stomach discomfort.	
General Advice	•	tly closed	nal, or local

Hazard Not Otherwise Classified (HNOC) Not applicable

#### COMPOSITION/INFORMATION ON INGREDIENTS 3.

Chemical Name	CAS Number	Weight %	Trade Secret
Limestone	1317-65-3	20-40	*
Asphalt	8052-42-4	20-40	*
Quartz	14808-60-4	<20	*
Kaolin	1332-58-7	<10	*
Bentonite	1302-78-9	<10	*

\*The exact percentage of composition has been withheld as a trade secret.

**FIRST AID MEASURES** 4. **Description of Necessary First-Aid Measures** Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician. Skin Contact Wash off immediately with soap and plenty of water. In the case of skin irritation or allergic reactions, see a physician. Move to fresh air. If symptoms persist, call a physician. Inhalation Drink plenty of water. Do NOT induce vomiting. Never give anything by mouth to an Ingestion unconscious person. Consult a physician if necessary. Most Important Symptoms/Effects, Acute and Delayed Most Important Symptoms/Effects No information available Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary Treat Symptomatically. May cause sensitization by skin contact. Notes to Physician 5. FIRE-FIGHTING MEASURES Suitable Extinguishing Media Carbon Dioxide (CO2). Dry Chemical. Foam. Water Fog. Unsuitable Extinguishing Media CAUTION: Use of water spray when fighting fire may be inefficient. Specific Hazards Arising from the Chemical No information available Explosion Data Sensitivity to Mechanical Impact None Sensitivity to Static Discharge None Protective Equipment and Precautions for Firefighters As in any fire, wear self-contained breathing apparatus pressure- demand MSHA/NIOSH (approved or equivalent) and full protective gear. ACCIDENTAL RELEASE MEASURES 6. Personal Precautions, Protective Equipment, and EmergencyProcedures **Personal Precautions:** Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment. **Environmental Precautions Environmental Precautions:** See Section 12 for additional Ecological Information Methods and Materials for Containment and Cleaning Up **Methods for Containment:** Prevent further leakage or spillage if safe to do so. Methods for Cleaning Up: Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. HANDLING AND STORAGE 7. **Precautions for Safe Handling** Handling: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes, and clothing. Wear personal protective equipment. Avoid breathing vapors or mists. Do not eat, drink, or smoke when using this product. Wash thoroughly after handling. Conditions for Safe Storage, Including Any Incompatibilities Storage: Keep container tightly closed **Incompatible Products:** Strong oxidizing agents. Acids. **EXPOSURE CONTROLS / PERSONAL PROTECTION** 8.

Control Parameters Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Limestone 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> (vacated) TWA: 15 mg/m <sup>3</sup> (vacated) TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> respirable dust TWA 10 mg/m <sup>3</sup> total dust
Asphalt 8052-42-4	TWA: 0.5 mg/m <sup>3</sup> benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m³ fume 15 min.
Quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable fraction	30/(%SiO2+2) mg/m <sup>3</sup> TWA, Total Dust; 250/(%SiO2+5) mppcf TWA, respirable fraction; 10/(%SiO2+2) mg/m <sup>3</sup> TWA, respirable TWA: 0.1 mg/m <sup>3</sup> (vacated)	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust
Kaolin 1332-58-7	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA 5 mg/m <sup>3</sup> respirable fraction	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable dust
Bentonite 1302-78-9	TWA 1 mg/m <sup>3</sup> respirable fraction	-	-

# Appropriate Engineering Controls Engineering Measures:

Showers Eyewash Stations Ventilation Systems

Individual Protection Measures, such as Personal Protective Equipment				
Eye/Face Protection: Skin and Body Protection: Respiratory Protection:	If splashes are likely to occur, wear: Safety glasses with side shields. Impervious gloves. No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.			
Hygiene Measures:	Handle in accordance with good industrial hygiene and safety practice.			

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State:	Liquid		Appearance:	Black
Odor:	Asphaltic		Odor Threshold:	No Information Available
Property		Values	Remark	s/Method
рН		No data available	None kn	own
Melting Point/Ran	ge	No data available	None kn	own
Boiling Point/Boili	ing Range	100° C	None kn	own
Flash Point		No data available	None kn	own
Evaporation Rate		No data available	None kn	own
Flammability (solid	d, gas)	No data available	None kn	own
Flammability Limi	ts in Air			
Upper flammab	oility limit	No data available		
Lower flammat	pility limit	No data available		
Vapor Pressure		No data available	None kn	own
Vapor Density		No data available	None kn	own
Specific Density		1.28 @ 77 F	None kn	own
Water Solubility		Easily dispersible	None kn	own
Solubility in other	solvents	No data available	None kn	own
Partition coefficie	nt: n-octanol/water	No data available	None kn	own
Autoignition Temp	perature	No data available	None kn	own
Decomposition Te	emperature	No data available	None kn	own
Viscosity		No data available	None kn	own
Flammable Proper	rties	Not Flammable		
Explosive Propert	ies	No data available		
Oxidizing Properti	es	No data available		
VOC Content		Less than 15 g/l		

#### **10. STABILITY AND REACTIVITY**

Reactivity:	No data available
Chemical Stability:	Stable under recommended storage conditions.
Possibility of Hazardous Reactions:	None under normal processing.
Hazardous Polymerization:	Hazardous polymerization does not occur.
Conditions to Avoid:	None known
Incompatible Materials:	Strong oxidizing agents. Acids.
Hazardous Decomposition Products	: Carbon Monoxide (CO), Carbon Dioxide (CO <sup>2</sup> ), Hydrogen Sulfide, Nitrogen Dioxide

### **11. TOXICOLOGICAL INFORMATION**

## Information on Likely Routes of Exposure

**Product Information** 

Inhalation: May cause irritation of respiratory tract. Contact with eyes may cause irritation. Eye Contact: Skin Contact: May cause irritation. Ingestion may cause stomach discomfort. Ingestion:

Chemical Name	LD50 Oral	LD50 Dermal	LD50 Inhalation
Asphalt	5000 mg/kg (Rat)	>2000 mg/kg (Rabbit)	-
Quartz	500 mg/kg (Rat)		
Bentonite	>5000 mg/kg (Rat)	-	-

#### Symptoms Related to the Physical, Chemical, and Toxicological Characteristics Symptoms:

No information available.

#### Delayed and Immediate Effects and also Chronic Effects from Short and Long Term Exposure

Sensitization: No information available. Mutagenic Effects: No information available. Carcinogenicity: The table below indicates whether each agency has listed any ingredient as a carcinogen. The IARC, NTP, and OSHA do not list asphalt as a carcinogen. In general, the oxidation of polycyclic aromatic hydrocarbons destroys their carcinogenic potential. Petroleum asphalt. shale oil asphalts, and coal tars show distinct variation in their relative carcinogenicity for experimental animals. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt	A3	Group 2B	Reasonably Anticipated	Х
Quartz	A2	Group 1	Known	Х

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 – Animal Carcinogen A2 – Suspected Human Carcinogen IRAC: (International Agency for Research on Cancer) Group 2B – Possibly Carcinogenic to Humans Group 1 - Carcinogenic to Humans NTP: (National Toxicity Program) Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen Known – Known Human Carcinogen OSHA: (Occupational Safety & Health Administration) X - Present

Reproductive Toxicity:	No information available.
STOT - Single Exposure:	No information available.
STOT – Repeated Exposure:	No information available.
Aspiration Hazard:	No information available.

#### Numerical Measures of Toxicity – Product

The following values are calculated based on Chapter 3.1 of the GHS document LD50 Oral: 12542 mg/kg; Acute toxicity estimate LD50 Dermal 6181 mg/kg, Acute toxicity estimate

#### 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Bentonite 1302-78-9		LC50 96 h: 8.0-19.0 g/L (Salmo gairdneri) LC50 96 h: = 19000 mg/L static (Oncorhynchus mykiss)		

#### Persistence and Degradability: Bioaccumulation

No information available.

Diodobalitatation		
Chemical Name	Log Pow	
Asphalt	6.006	

**Other Adverse Effects:** 

No information available.

	13. DISPOSAL CONSIDERATIONS	
Waste Disposal Methods:	This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.	
Contaminated Packaging:	Do not re-use empty containers.	
	14. TRANSPORTATION INFORMATION	
DOT:	Not regulated	
15. REGULATORY INFORMATION		

#### International Inventories

TSCA – Complies DSL/NDSL – Complies

#### Legend

TSCA – United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL – Canadian Domestic Substances List/Non-Domestic Substances List

#### U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS Number	Weight %	SARA 313 – Threshold Values %
Asphalt	8052-42-4	20-40	0.1

#### SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

# Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

# <u>CERCLA</u>

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific requirements at the local, regional, or state level pertaining to releases of this material.

## **U.S. State Regulations**

#### **California Proposition 65:**

Chemical Name	CAS Number	California Prop. 65
Quartz	14808-60-7	Carcinogen

<u>U.S. State Right-To-Know Regulations</u> "X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Limestone	Х	Х	Х		Х
Asphalt	Х	Х	Х		Х
Quartz	Х	Х	Х	-	Х
Kaolin	Х	Х	Х		Х
Carbon Black	Х	Х	Х	Х	Х

Not applicable

### U.S. EPA Label Information

EPA Pesticide Registration Number:

	16. OTHER INFORMATION			
<u>NFPA</u>	Health Hazard: 1	Flammability: 0	Instability: 0	Physical and Chemical Hazards-
<u>HMIS</u>	Health Hazard: 1	Flammability: 0	Physical Hazard: 0	Personal Protection: X
Revision Date: Revision Note:	6-Jan-2016 Supersedes 1	5-December-2014.		

Revision Note: Supersedes 15-December-2	nevision Date.	0-Jan-2010
	Revision Note:	Supersedes 15-December-2

<u>General Disclaimer</u> The information provided on this SDS is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.